

ESPECIFICACIONES TECNICAS DE BATERIAS POWER SONIC									
Linea Standard - 5 años									
Modelo Bateria	Tensión Nominal Volts	Capacidad Nominal en 20Hs @1,75Vpc a 25°C	Capacidad en 10Hs @1,75Vpc a 25°C	Dimensiones (mm)				Peso (Kg)	Terminales
				Largo	Ancho	Alto	Alto c/ bornes		
PS-640	6	4,5	4,0	70	47	102	102	0,9	F ó WL
PS-6100	6	12,0	11,5	151	51	94	98	2,09	TS ó WL
PS-6120	6	12,0	11,0	108	70	141	141	2,4	F, TH ó TS
PS-1250	12	5,0	4,7	90	70	102	107	1,9	F1 ó F2
PSH-1255	12	5,5	4,8	90	70	101	106	1,8	F2
PS-1270	12	7,0	6,5	151	65	94	98	2,6	F1
PS-12120	12	12,0	11,0	151	98	94	100	4,1	F2
PS-12180	12	18,0	17,0	181	76	167	167	5,9	F2 ó NB
PS-12260	12	26,0	24,5	175	166	126	126	9,4	F2 ó NB
PS-12330	12	35,0	33,0	198	132	158	180	10,9	NB
PS-12400	12	40,0	37,0	196	163	174	174	14,7	NB
PS-12550	12	55,0	49,0	230	138	207	228	18,2	NB
PS-12750	12	80,0	75,0	260	168	207	228	26,4	NB
PS-121000	12	100,0	95,0	305	168	207	228	30,8	NB
Linea Power Guard Series- 10 años									
Modelo Bateria	Tensión Nominal Volts	Capacidad Nominal en 10Hs @1,80Vpc a 25°C	Capacidad en 20Hs @1,80Vpc a 25°C	Dimensiones (mm)				Peso (Kg)	Terminales
				Largo	Ancho	Alto	Alto c/ bornes		
PG-6V210	6	210,0	226,0	374	170	210	217	36,0	Inserto roscado
PG-12V103	12	103,0	110,0	330	173	212	220	32,0	Inserto roscado
PG-12V120	12	120,0	129,0	410	177	211	225	37,6	Inserto roscado
PG-12V150	12	153,0	166,0	485	170	242	242	48,2	Inserto roscado
PG-12V200	12	210,0	226,0	522	240	218	224	64,0	Inserto roscado
Linea Power Guard Series- 15 años									
Modelo Bateria	Tensión Nominal Volts	Capacidad Nominal en 10Hs @1,80Vpc a 25°C	Capacidad en 20Hs @1,80Vpc a 25°C	Dimensiones (mm)				Peso (Kg)	Terminales
				Largo	Ancho	Alto	Alto c/ bornes		
PG-2V100	2	100	110	170	98	205	212	7,5	Inserto roscado
PG-2V200	2	216	236	170	110	328	350	13,7	Bornes
PG-2V250	2	252	284	170	110	328	350	19,0	Bornes
PG-2V300	2	324	352	170	150	328	350	19,3	Bornes
PG-2V400	2	432	468	210	175	330	350	27,0	Bornes
PG-2V500	2	525	568	240	170	330	350	31,0	Bornes
PG-2V600	2	600	650	300	175	330	350	40,0	Bornes
PG-2V800	2	800	868	410	175	330	351	56,0	Bornes
PG-2V1000	2	1050	1086	475	173	328	350	66,0	Bornes
PG-2V2000	2	2000	2170	490	350	343	375	136,0	Bornes
PG-2V3000	2	3000	3254	712	350	343	375	212,0	Bornes